

















COMPACT, PORTABLE METAL TAG EMBOSSER

The **ME550 FLEXI TAG** is a portable metal tag embossing solution designed to emboss a variety of sizes, materials, shapes and thicknesses. The machine is equipped with an adjustable input hopper which can adapt to different plate sizes based on application requirements. With a 10% increase in production speed, a completely renewed design and new features, the **ME550 FLEXI TAG** is an advanced solution that can be integrated into any existing factory or office network.

7" color touchscreen display with high resolution

The **ME550 FLEXI TAG** is equipped with a built-in 7 "WVGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way.

IoT (Internet of Things) remote access and management

- **Web services:** The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.
- **Data transfer:** Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

USB (type A, type B), Ethernet and WiFi

The **ME550 FLEXI TAG** can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

The **ME550 FLEXI TAG** is a completely self-contained tag marking machine that is easy to transport and designed to operate in harsh industrial environments. It is ideal for component and production line identification and traceability applications.



- AUTOMOTIVE PLANTS
- SHIPYARDS
- STEEL PLANTS
- MILITARY
- LOGISTICS MENAGEMENT
- INDUSTRIAL MANUFACTURERS



- BODY & VIN PLATES
- MILITARY ID TAGS
- INVENTORY
- ASSET CONTROL
- ID & TRACKING TAGS
- CABLE / HOSE TAGS
- TAGS FOR GALVANIZED OR HEAT-TREATED PROCESSES
- COMPONENT ID
- SERIAL NUMBER TAGS

PLATE AND FEEDER

Dimensions Rectangular tag: $52 \times 29 \div 65 \times 60 \text{ mm} - 2.05 \times 1.14 \div 2.56 \times 2.36 \text{ in (WxH)}$





min. 52 x 29 mm - 2,05 x 1,14 in

max. 65 x 60 mm - 2.56 x 2.36 in

Materials Alluminum, stainless steel

Thickness $0,3556 \div 0,70 \text{ mm} - 0.014 \div 0.0275 \text{ in}$

Input hopper Up to 250 plates capacity (0,4 mm / 0.0157 in) - automatic feed only

Output hopper External collection tray

MARKING

Technology Embossing or debossing

Wheel capacity 60 slots

Type set Simplex 2, Block USA, Block 5, OCRB1
Embossing area See picture. Up to 10 lines / 20 characters

Performance 105 tags per hour based on 55 characters (144 tags per hour based on 45 characters)

COMMUNICATION AND SOFTWARE

Interface USB 2.0 port (device and host), Ethernet. WiFi (optional)
Software PowerTag PC application proprietary software compatible with

Windows 8.1/10/11, MacOS (Intel64, da 10.x onwards), Linux

PowerTag USB on USB key for multiple use

Protocol Multiembosser

Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound

HARDWARE

System CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based

Power supply Universal switching power supply 100-240 Volts; 50 or 60 Hz

Power consumption 300 Watt max

Operating environment Temperature: 5°÷ 40°C 7 / 41°÷104° F, relative humidity 30% ÷ 90%

VARIOUS

Others Built in touch screen 7", multi-language user interface management: English, Spanish, Italian

Innovative embedded software up-grade system thru pen drive and web server Machine configuration protected by password for high security and data protection

Easy to carry handle, no packaging required


CERTIFICATIONS














EMBOSSING AREA



Dashed area not usable height 3,5 mm - 0.137 in





WEIGHT

26 Kg / 57.3 lbs



