



TOUCH
SCREEN 7"



INTERNET
OF THINGS



WIFI



USB



ETHERNET



**METAL
PLATE**
Systems

COMPACT, PORTABLE CR80 METAL TAG EMBOSSE

The **ME550 CR80** is a portable metal tag embosser designed to manage **CR80** tag sizes (85,6 mm x 54 mm / 3.37" x 2.13") ideal for permanent marking of aluminum and stainless steel tags. With a 10% increase in production speed, a completely renewed design and new features, the **ME550 CR80** is an advanced solution that can be integrated into any existing factory or office network.

7" color touchscreen display with high resolution

The **ME550 CR80** is equipped with a built-in 7" WVGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way.

IoT (Internet of Things) remote access and management

- Web services: The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.

- Data transfer: Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

USB (type A, type B), Ethernet and WiFi

The **ME550 CR80** can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

The **ME550 CR80** is a completely self-contained tag marking machine, and is ideal for component and production line identification and traceability applications. Designed to operate in harsh industrial environments and easy to transport.



USED BY

- AUTOMOTIVE PLANTS
- SHIPYARDS
- STEEL PLANTS

- INDUSTRIAL MANUFACTURERS
- LOGGING INDUSTRIES
- LOGISTICS MANAGEMENT
- POWER & UTILITY COMPANIES



IDEAL FOR

CR80 SIZE

FEATURES AND SPECIFICATIONS

MODEL NAME

ME550 CR80

PLATE AND FEEDER

Dimensions



31



41



42



43

Materials

Thickness

Input hopper

Output hopper

Alluminum, stainless steel

Metal plates: 0,356 ÷ 0,70 mm / 0.014 ÷ 0.0275 in

Up to 120 plates capacity (0,4 mm / 0.0157 in)

External collection tray

MARKING

Technology

Embossing or debossing

Wheel capacity

60 slots

Type set

Simplex 2, Block USA, Block 5, OCRB1

Embossing area

See picture

Performance

120 tags per hour based on 55 characters (112 tags per hour based on 60 characters)

COMMUNICATION AND SOFTWARE

Interface

USB 2.0 port (device and host), Ethernet, WiFi (optional)

Software

PowerTag PC application proprietary software compatible with

Windows 8.1/10/11, MacOS (Intel64, da 10.x onwards), Linux

PowerTag USB on USB key for multiple use

Protocol

Multiembosser

Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound

HARDWARE

System

CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based

Power supply

Universal switching power supply 100-240 volts; 50 or 60 hz

Power consumption

300 Watt max

Operating environment

Temperature: 5°÷ 40°C / 41°÷104°F, relative humidity 30% ÷ 90%

VARIOUS

Others

Built in touch screen 7", multi-language user interface management: English, Spanish, Italian
Innovative embedded software up-grade system thru pen drive and web server
Interchangeable input hopper for easy charge and discharge of medical alert & dog tags
Machine configuration protected by password for high security and data protection
Easy to carry handle, no packaging required


CERTIFICATIONS



WARRANTY



EMBOSSING AREA



DIMENSION



WEIGHT

26 Kg / 57.3 lbs



SOFTWARE

powertag LITE

optional

powertag EVO